

41 – 45 Tarnard Drive, Braeside, VIC 3195 131 Garling Street, O'Connor, WA 6163 Telephone: 1800 334 679 A division of George Weston

JAFLOC AE49

Polymer Flocculant



FEATURES

- Water conditioning
- Compatible with mineral coagulants
- Removal of colloidal material

AREAS OF USE

- Industrial water treatment
- Waste water treatment
- Municipal water treatment

DESCRIPTION

JAFLOC AE49 is a polyacrylamide solution used for water treatment in various industries.

DIRECTIONS FOR USE

The dose rate of JAFLOC AE49 will depend upon a number of factors. For assessment before use, please consult your Jasol representative.

SAFETY INFORMATION

JAFLOC AE49 is NOT classified as Hazardous according to the GHS.

JAFLOC AE49 is NOT classified as Dangerous Goods according to the ADG Code (7th Ed).

JAFLOC AE49 is NOT a Scheduled Poison according to the SUSMP.

FIRST AID INFORMATION

For advice in an emergency, contact **Poisons Information Centre Australia (phone 13 11 26) or a doctor at once.** If swallowed do NOT induce vomiting. Wash out mouth thoroughly with water. If in eyes, hold eyelids apart and flood with water for at least 15 minutes. Seek medical attention if irritation persists.

24 HOUR TOLL FREE EMERGENCY PHONE NO: 1800 629 953

PRODUCT ENQUIRIES

Customer Service: 1800 334 679 jasolcsteam@gwf.com.au

For further information regarding product safety and handling, refer to the Safety Data Sheet and product label.

PHYSICAL & CHEMICAL PROPERTIES

FORM Viscous Liquid COLOUR Milky 5.0 - 8.0рΗ IONIC CHARACTER Anionic CHARGE DENSITY Medium MOLECULAR WEIGHT High SPECIFIC GRAVITY 1.00 - 1.10Av. NON-VOLATILE SOLIDS 34 - 41% **BULK VISCOSITY** 500 - 2000 cps MAX. CONCENTRATION 10g/L STABILITY OF D.I. SOLUTIONS 8 Days

Approx. BULK DENSITY @ 5g/L 2400 cps

STORAGE TEMPERATURE 5-35°C (5-30°C inside building)

SHELF LIFE 6 months

25Kg



Last Modified: 20/02/2025 Revision: 2.0

Printed version is Un-Controlled Page 1