

41 – 45 Tarnard Drive, Braeside, VIC 3195 131 Garling Street, O'Connor, WA 6163 Telephone: 1800 334 679 A division of George Weston

WATER TREATMENT

JAFLOC CESC79

Polymer Flocculant

FEATURES

- Water conditioning
- Compatible with mineral coagulants
- Removal of colloidal material

AREAS OF USE

- Industrial water treatment
- Waste water treatment
- Municipal water
 treatment

PRODUCT ENQUIRIES

Customer Service: 1800 334 679 jasolcsteam@gwf.com.au

For further information regarding product safety and handling, refer to the Safety Data Sheet and product label.

DESCRIPTION

JAFLOC CESC79 is a very high density charge polyacrylamide solution used for waste water flocculation in various industries.

DIRECTIONS FOR USE

The dose rate of JAFLOC CESC79 will depend upon a number of factors. For assessment before use, please consult your Jasol representative.

SAFETY INFORMATION

JAFLOC CESC79 is NOT classified as Hazardous according to the GHS. JAFLOC CESC79 is NOT classified as Dangerous Goods according to the ADG Code (7th Ed). JAFLOC CESC79 is NOT a Scheduled Poison according to the SUSMP.

FIRST AID INFORMATION

For advice in an emergency, contact **Poisons Information Centre Australia (phone 13 11 26) or a doctor at once.** If swallowed do NOT induce vomiting. Wash out mouth thoroughly with water. If in eyes, hold eyelids apart and flood with water for at least 15 minutes. Seek medical attention if irritation persists.

24 HOUR TOLL FREE EMERGENCY PHONE NO: 1800 629 953

PHYSICAL & CHEMICAL PROPERTIES

FORM COLOUR pH IONIC CHARACTER CHARGE DENSITY MOLECULAR WEIGHT SPECIFIC GRAVITY Av NON-VOLATILE SOLIDS BULK VISCOSITY MAX. CONCENTRATION STABILITY OF D.I. SOLUTIONS DILUTION TO OBTAIN 5g/L STORAGE TEMPERATURE Opaque Liquid Milky 4.0-6.0 (@5g/L) Cationic Very High High 1.05 50% 1200 cps 5g/L 1 day 90 0-35°C





Providing hygiene service solutions since 1934