



41 – 45 Tarnard Drive, Braeside, VIC 3195
131 Garling Street, O'Connor, WA 6163
Telephone: 1800 334 679
A division of George Weston

JAFLOC CP59

Polymer Flocculant



FEATURES

- Water conditioning
- Compatible with mineral coagulants
- Removal of colloidal material

AREAS OF USE

- Industrial water treatment
- Waste water treatment
- Municipal water treatment

DESCRIPTION

JAFLOC CP59 is a high density charge polyacrylamide powder used for waste water flocculation in various industries.

DIRECTIONS FOR USE

The dose rate of JAFLOC CP59 will depend upon a number of factors. For assessment before use, please consult your Jasol representative.

SAFETY INFORMATION

JAFLOC CP59 is NOT classified as Hazardous according to the GHS.
JAFLOC CP59 is NOT classified as Dangerous Goods according to the ADG Code (7th Ed).
JAFLOC CP59 is NOT a Scheduled Poison according to the SUSMP.

FIRST AID INFORMATION

For advice in an emergency, contact **Poisons Information Centre Australia (phone 13 11 26) or a doctor at once**. If swallowed do NOT induce vomiting. Wash out mouth thoroughly with water. If in eyes, hold eyelids apart and flood with water for at least 15 minutes. Seek medical attention if irritation persists.

24 HOUR TOLL FREE EMERGENCY PHONE NO: 1800 629 953

PRODUCT ENQUIRIES

Customer Service: **1800 334 679**

jasolcsteam@gwf.com.au

For further information regarding product safety and handling, refer to the Safety Data Sheet and product label.

PHYSICAL & CHEMICAL PROPERTIES

FORM	Granular Powder
COLOUR	White
MESH SIZE (% >10 mesh)	2
MESH SIZE (% <100 mesh)	6
IONIC CHARACTER	Cationic
CHARGE DENSITY	High
MOLECULAR WEIGHT	Ultra High
pH	2.5-4.5 (@5 g/L)
Approx. BULK DENSITY	0.8
MAX. CONCENTRATION	5 g/L
DISSOLUTION TIME in DI water	90 minutes
STABILITY OF D.I. SOLUTIONS	1 day
RECOMMENDED WORKING CONC	3 g/L
STORAGE TEMPERATURE	0-35°C
SHELF LIFE	24 months

15Kg

2144070

Providing hygiene service solutions since 1934