



# JAFLOC CP79

## Polymer Flocculant



### FEATURES

- Water conditioning
- Compatible with mineral coagulants
- Removal of colloidal material

### AREAS OF USE

- Industrial water treatment
- Waste water treatment
- Municipal water treatment

### DESCRIPTION

JAFLOC CP79 is a very high density charge polyacrylamide powder used for waste water flocculation in various industries.

### DIRECTIONS FOR USE

The dose rate of JAFLOC CP79 will depend upon a number of factors. For assessment before use, please consult your Jasol representative.

### SAFETY INFORMATION

JAFLOC CP79 is NOT classified as Hazardous according to the GHS.

JAFLOC CP79 is NOT classified as Dangerous Goods according to the ADG Code (7<sup>th</sup> Ed).

JAFLOC CP79 is NOT a Scheduled Poison according to the SUSMP.

#### FIRST AID INFORMATION

For advice in an emergency, contact **Poisons Information Centre Australia (phone 13 11 26)** or **a doctor at once**. If swallowed do NOT induce vomiting. Wash out mouth thoroughly with water. If in eyes, hold eyelids apart and flood with water for at least 15 minutes. Seek medical attention if irritation persists.

**24 HOUR TOLL FREE EMERGENCY PHONE NO: 1800 629 953**

### PRODUCT ENQUIRIES

Customer Service: **1800 334 679**

[jasolcsteam@gwf.com.au](mailto:jasolcsteam@gwf.com.au)

For further information regarding product safety and handling, refer to the Safety Data Sheet and product label.

### PHYSICAL & CHEMICAL PROPERTIES

FORM	Granular Solid
COLOUR	White
MESH SIZE (% >10 mesh)	2
MESH SIZE (% <100 mesh)	10
IONIC CHARACTER	Cationic
CHARGE DENSITY	Very High
MOLECULAR WEIGHT	High
Approx. BULK DENSITY	0.8
MAX. CONCENTRATION	5g/L
DISSOLUTION TIME in DI water	120 minutes
STABILITY OF D.I. SOLUTIONS	1 day
RECOMMENDED WORKING CONC	3g/L
STORAGE TEMPERATURE	0-35°C
SHELF LIFE	24 months

15Kg

2144021

