



41 – 45 Tarnard Drive, Braeside, VIC 3195
131 Garling Street, O'Connor, WA 6163
Telephone: 1800 334 679
A division of George Weston

JAFLOC LBCESC79

Polymer Flocculant



FEATURES

- Water conditioning
- Compatible with mineral coagulants
- Removal of colloidal material

AREAS OF USE

- Industrial water treatment
- Waste water treatment
- Municipal water treatment

DESCRIPTION

JAFLOC LBCESC79 is a very high density charge polyacrylamide solution used for waste water flocculation in various industries.

DIRECTIONS FOR USE

The dose rate of JAFLOC LBCESC79 will depend upon a number of factors. For assessment before use, please consult your Jasol representative.

SAFETY INFORMATION

JAFLOC LBCESC79 is NOT classified as Hazardous according to the GHS.
JAFLOC LBCESC79 is NOT classified as Dangerous Goods according to the ADG Code (7th Ed).
JAFLOC LBCESC79 is NOT a Scheduled Poison according to the SUSMP.

FIRST AID INFORMATION

For advice in an emergency, contact **Poisons Information Centre Australia (phone 13 11 26)** or **a doctor at once**. If swallowed do NOT induce vomiting. Wash out mouth thoroughly with water. If in eyes, hold eyelids apart and flood with water for at least 15 minutes. Seek medical attention if irritation persists.

24 HOUR TOLL FREE EMERGENCY PHONE NO: 1800 629 953

PRODUCT ENQUIRIES

Customer Service: **1800 334 679**
jasolcsteam@gwf.com.au

For further information regarding product safety and handling, refer to the Safety Data Sheet and product label.

PHYSICAL & CHEMICAL PROPERTIES

FORM	Opaque Liquid
COLOUR	Milky
pH	4.0-6.0 (@5g/L)
IONIC CHARACTER	Cationic
CHARGE DENSITY	Very High
MOLECULAR WEIGHT	High
SPECIFIC GRAVITY	1.05
Av NON-VOLATILE SOLIDS	50%
BULK VISCOSITY	1200 cps
MAX. CONCENTRATION	5g/L
STABILITY OF D.I. SOLUTIONS	1 day
DILUTION TO OBTAIN 5g/L	90
STORAGE TEMPERATURE	0-35°C

1000L
2144082

Providing hygiene service solutions since 1934