

pH Adjustment

FEATURES

- Highly concentrated
- Rapid pH adjustment • response

AREAS OF USE

Water treatment plants

DESCRIPTION

LC-32 is a heavy duty alkaline solution used for pH adjustment in water treatment units and CIP circulation cleaning.

DIRECTIONS FOR USE

CIP Circulation: Use at a rate of 0.3-1.5%v/v depending on soiling and application.

Wastewater Treatment: The use rates depend upon a number of factors, such as application, desired pH and the type of system.

Please, consult your Jasol representative for further information.

SAFETY INFORMATION

LC-32 is classified as Hazardous according to the GHS. LC-32 is classified as Dangerous Goods according to the ADG Code (7th Ed). LC-32 is a Scheduled Poison according to the SUSMP. Avoid contact with eyes and skin. Refer to SDS for further information.

FIRST AID INFORMATION

For advice in an emergency, contact Poisons Information Centre (Phone Australia 13 11 26) or a doctor at once. If swallowed do NOT induce vomiting. Wash out mouth thoroughly with water and seek immediate medical attention. If in eyes, hold eyelids apart and flood with water for at least 15 minutes. If on skin, remove contaminated clothing and wash affected area with running water. Seek immediate medical attention if irritation persists.

24 HOUR TOLL FREE EMERGENCY PHONE NO: 1800 629 953

PRODUCT ENQUIRIES

Customer Service: 1800 334 679 jasolcsteam@gwf.com.au

For further information regarding product safety and handling, refer to the Safety Data Sheet and product label.

FORM
COLOUR
ODOUR
рН
SPECIFIC GRAVITY
FLAMMABILITY

Clear Liquid Colourless Odourless >12.0 1.35 at 20°C Not Flammable

PHYSICAL & CHEMICAL PROPERTIES





41 - 45 Tarnard Drive, Braeside, VIC 3195 131 Garling Street, O'Connor, WA 6163 Telephone: 1800 334 679 A division of George Weston



Last Modified: 20/02/2025 Printed version is Un-Controlled