PROTREAT 810

Alkalinity Builder

WATER TREATMENT

FEATURES

- Highly concentrated liquid alkaline
- Cost effective
- Easy and accurate dosing
- HALAL approved

AREAS OF USE

- Water treatment
- Boiler
- Cooling system
- Effluent stream

PRODUCT ENQUIRIES

Customer Service: **1800 334 679**
jasolcsteam@gwf.com.au

For further information regarding product safety and handling, refer to the Safety Data Sheet and product label.

DESCRIPTION

PROTREAT 810 is an alkalinity builder for water treatment. It is a concentrated alkaline solution used for controlling or increasing the pH or alkalinity of water in boilers, cooling systems and effluent streams.

DIRECTIONS FOR USE

The dosage rate for PROTREAT 810 will depend upon a number of factors, including the type and volume of the system being treated and desired degree of alkalinity or pH.

For assessment before use, please consult your Jasol representative.

SAFETY INFORMATION

PROTREAT 810 is classified as Hazardous according to the GHS.
PROTREAT 810 is classified as Dangerous Goods according to the ADG Code (7th Ed).
PROTREAT 810 is a Scheduled Poison according to the SUSMP.
Avoid contact with eyes and skin. Refer to SDS for further information.

FIRST AID INFORMATION

If poisoning occurs contact a doctor or **Poisons Information Centre Australia, Phone 13 11 26.** If swallowed do NOT induce vomiting. Wash out mouth thoroughly with water and seek immediate medical attention. If in eyes, hold eyelids apart and flood with water for at least 15 minutes. If on skin, remove contaminated clothing and wash affected area with running water. Seek immediate medical attention.

24 HOUR TOLL FREE EMERGENCY PHONE NO: 1800 629 953

PHYSICAL & CHEMICAL PROPERTIES

FORM	Liquid
COLOUR	Colourless
ODOUR	Odourless
pH	>13.0
SPECIFIC GRAVITY	1.50 at 20°C
FLAMMABILITY	Not Flammable

15L 2140300
200L 2140301

Providing hygiene service solutions since 1934