

41 – 45 Tarnard Drive, Braeside, VIC 3195 131 Garling Street, O'Connor, WA 6163 Telephone: 1800 334 679 A division of George Weston

WATER TREATMENT

PROTREAT BFW82F

Corrosion Inhibitor

FEATURES

- One-shot treatment
- Cost effective
- Easy and accurate dosing

AREAS OF USE

- Water treatment
- Boiler water treatment
- Sludge treatment

DESCRIPTION

PROTREAT BFW82F is a one-shot boiler scale and corrosion inhibitor and sludge conditioner.

DIRECTIONS FOR USE

PROTREAT BFW82F can be used neat or as a dilute solution. Best results would be obtained with hot water dilution. It is compatible with most of Jasol products with a few exceptions.

Please, consult your Jasol representative for further information.

SAFETY INFORMATION

PROTREAT BFW82F is classified as Hazardous according to the GHS.
PROTREAT BFW82F is classified as Dangerous Goods according to the ADG Code (7th Ed).
PROTREAT BFW82F is a Scheduled Poison according to the SUSMP.
Avoid contact with eyes and skin. Refer to SDS for further information.

FIRST AID INFORMATION

If poisoning occurs contact a doctor or **Poisons Information Centre Australia, Phone 13 11 26.** If swallowed do NOT induce vomiting. Wash out mouth thoroughly with water and seek immediate medical attention. If in eyes, hold eyelids apart and flood with water for at least 15 minutes. If on skin, remove contaminated clothing and wash affected area with running water. Seek immediate medical attention.

24 HOUR TOLL FREE EMERGENCY PHONE NO: 1800 629 953

PRODUCT ENQUIRIES

Customer Service: **1800 334 679** jasolcsteam@gwf.com.au

For further information regarding product safety and handling, refer to the Safety Data Sheet and product label.

PHYSICAL & CHEMICAL PROPERTIES

FORM Clear Liquid
COLOUR Colourless to Straw
ODOUR Odourless
pH 12.0-13.5

SPECIFIC GRAVITY 1.13 at 20°C
FLAMMABILITY Not Flammable





Last Modified: 20/02/2025 Revision: 2.0

Printed version is Un-Controlled Page 1