



41 – 45 Tarnard Drive, Braeside, VIC 3195  
131 Garling Street, O'Connor, WA 6163  
Telephone: 1800 334 679  
A division of George Weston



# PROTREAT OS110

## Corrosion Inhibitor

### FEATURES

- Oxygen scavenger
- Cost effective
- For low-medium pressure boilers
- HALAL approved

### AREAS OF USE

- Boiler water treatment

### DESCRIPTION

PROTREAT OS110 is a sodium metabisulphite based product designed to prevent corrosion in steam generating systems by absorbing oxygen from feedwater and boiler water. It is effective at high feedwater temperatures and suitable for low-medium pressure systems.

### DIRECTIONS FOR USE

PROTREAT OS110 should be dosed continuously, as a dilute solution or neat, into the boiler feedwater. The dosage rate for PROTREAT OS110 will depend upon a number of factors.

Please, consult your Jasol representative for assessment before use.

### SAFETY INFORMATION

PROTREAT OS110 is classified as Hazardous according to the GHS.  
PROTREAT OS110 is classified as Dangerous Goods according to the ADG Code (7<sup>th</sup> Ed).  
PROTREAT OS110 is a Scheduled Poison according to the SUSMP.  
Avoid contact with eyes and skin. Refer to SDS for further information.

#### FIRST AID INFORMATION

If poisoning occurs contact a doctor or **Poisons Information Centre Australia, Phone 13 11 26**.  
If swallowed do NOT induce vomiting. Wash out mouth thoroughly with water and seek immediate medical attention. If in eyes, hold eyelids apart and flood with water for at least 15 minutes. If on skin, remove contaminated clothing and wash affected area with running water. Seek immediate medical attention.

**24 HOUR TOLL FREE EMERGENCY PHONE NO: 1800 629 953**

### PRODUCT ENQUIRIES

Customer Service: **1800 334 679**  
[jasolsteam@gwf.com.au](mailto:jasolsteam@gwf.com.au)

For further information regarding product safety and handling, refer to the Safety Data Sheet and product label.

**FORM**  
**COLOUR**  
**ODOUR**  
**pH**  
**SPECIFIC GRAVITY**  
**FLAMMABILITY**

Clear Liquid  
Water White to Light Amber  
Pungent  
5.0-6.0  
1.20 at 20°C  
Not Flammable

