



41 – 45 Tarnard Drive, Braeside, VIC 3195
131 Garling Street, O'Connor, WA 6163
Telephone: 1800 334 679
A division of George Weston

PROTREAT OS155

Corrosion Inhibitor



FEATURES

- Biodegradable
- Natural corrosion inhibition power of tannins
- Cost effective
- For low-medium pressure boilers
- Non-hazardous
- HALAL approved

AREAS OF USE

- Boiler water treatment

DESCRIPTION

PROTREAT OS155 is a blend of natural and synthetic organic materials which prevents corrosion in steam generating systems by absorbing oxygen from feedwater and boiler water and by forming a protective iron tannate layer on the boiler surfaces. PROTREAT OS155 is effective at low feedwater temperatures where the use of sulphite-based oxygen scavengers becomes impractical and uneconomical.

PROTREAT OS155 also protects the boiler against scale by inhibiting the formation of calcium carbonate crystals. It is suitable for low-medium pressure boilers.

DIRECTIONS FOR USE

PROTREAT OS155 should be dosed continuously, as a dilute solution or neat, into the boiler feedwater. Dosage should be controlled to give a boiler water tannin reserve of 100-200ppm. PROTREAT OS155 is compatible with all Jasol boiler treatment chemicals.

For assessment before use, please consult your Jasol representative.

SAFETY INFORMATION

PROTREAT OS155 is NOT classified as Hazardous according to the GHS.

PROTREAT OS155 is NOT classified as Dangerous Goods according to the ADG Code (7th Ed).

PROTREAT OS155 is NOT a Scheduled Poison according to the SUSMP.

FIRST AID INFORMATION

For advice in an emergency, contact **Poisons Information Centre Australia (phone 13 11 26) or a doctor at once**. If swallowed do NOT induce vomiting. Wash out mouth thoroughly with water. If in eyes, hold eyelids apart and flood with water for at least 15 minutes. Seek medical attention if irritation persists.

24 HOUR TOLL FREE EMERGENCY PHONE NO: 1800 629 953

PRODUCT ENQUIRIES

Customer Service: **1800 334 679**

jasolcsteam@gwf.com.au

For further information regarding product safety and handling, refer to the Safety Data Sheet and product label.

FORM

COLOUR

ODOUR

pH

SPECIFIC GRAVITY

FLAMMABILITY

Liquid

Dark Brown

Odourless

6.5-8.0

1.06 at 20°C

Not Flammable



2142020

