



PROTREAT OS156

Corrosion Inhibitor

FEATURES

- Natural corrosion inhibition power of tannins
- Cost effective
- pH adjustment functionality
- HALAL approved

AREAS OF USE

- Boiler water treatment

DESCRIPTION

PROTREAT OS156 is a blend of natural and synthetic organic materials combined with the power of caustic detergents designed prevent corrosion in steam generating systems with low alkalinity feedwater by absorbing oxygen and boiler water and by forming a protective iron tannate layer on the boiler surfaces.

DIRECTIONS FOR USE

PROTREAT OS156 should be dosed continuously, as a dilute solution or neat, into the boiler feedwater. Dosage should be controlled to give a boiler water tannin reserve of 100-200ppm. PROTREAT OS156 is compatible with all Jasol boiler treatment chemicals.

For assessment before use, please consult your Jasol representative.

SAFETY INFORMATION

PROTREAT OS156 is classified as Hazardous according to the GHS.
PROTREAT OS156 is classified as Dangerous Goods according to the ADG Code (7th Ed).
PROTREAT OS156 is a Scheduled Poison according to the SUSMP.
Avoid contact with eyes and skin. Refer to SDS for further information.

FIRST AID INFORMATION

If poisoning occurs contact a doctor or **Poisons Information Centre Australia, Phone 13 11 26**.
If swallowed do NOT induce vomiting. Wash out mouth thoroughly with water and seek immediate medical attention. If in eyes, hold eyelids apart and flood with water for at least 15 minutes. If on skin, remove contaminated clothing and wash affected area with running water. Seek immediate medical attention.

24 HOUR TOLL FREE EMERGENCY PHONE NO: 1800 629 953

PRODUCT ENQUIRIES

Customer Service: **1800 334 679**
jasolcsteam@gwf.com.au

For further information regarding product safety and handling, refer to the Safety Data Sheet and product label.

PHYSICAL & CHEMICAL PROPERTIES

FORM	Liquid
COLOUR	Dark Brown
ODOUR	Odourless
pH	>12.0
SPECIFIC GRAVITY	1.04 at 20°C
FLAMMABILITY	Not Flammable

