



41 – 45 Tarnard Drive, Braeside, VIC 3195
131 Garling Street, O'Connor, WA 6163
Telephone: 1800 334 679
A division of George Weston

STAINLESS STEEL OIL

Hard Surface Cleaner & Polish



FEATURES

- Multi-purpose cleaner & polish
- Deep shine lustre effect
- Surface protection
- Water repellent
- Economical

AREAS OF USE

- Stainless steel surfaces
- Leather
- Antique furniture
- Natural wood
- Teak

DESCRIPTION

STAINLESS STEEL OIL is a combination of paraffinic oils. It is designed for cleaning and polishing stainless steel non-food contacting surfaces. STAINLESS STEEL OIL can also be used to polish antique furniture, teak, natural wood and even leather surfaces as it nourishes timber and leather, helping to preserve it.

DIRECTIONS FOR USE

Ensure the surface is clean. Apply STAINLESS STEEL OIL with a rag. Wipe off excess oil.

Consult your Jasol representative for further information.

SAFETY INFORMATION

STAINLESS STEEL OIL is classified as Hazardous according to the GHS.
STAINLESS STEEL OIL is NOT a Dangerous Goods according to the ADG Code (7th Ed).
STAINLESS STEEL OIL is a Scheduled Poison according to the SUSMP.
Combustible liquid. May be fatal if swallowed and enters airways. Refer to SDS for further information.

FIRST AID INFORMATION

If poisoning occurs contact a doctor or **Poisons Information Centre Australia, Phone 13 11 26**. If swallowed do NOT induce vomiting. Wash out mouth thoroughly with water and seek immediate medical attention. If in eyes, hold eyelids apart and flood with water for at least 15 minutes. If on skin, remove contaminated clothing and wash affected area with running water. Seek immediate medical attention.

24 HOUR TOLL FREE EMERGENCY PHONE NO: 1800 629 953

PRODUCT ENQUIRIES

Customer Service: **1800 334 679**

jasolcsteam@gwf.com.au

For further information regarding product safety and handling, refer to the Safety Data Sheet and product label.

PHYSICAL & CHEMICAL PROPERTIES

FORM	Clear Liquid
COLOUR	Colourless
ODOUR	Characteristic Hydrocarbon Odour
SPECIFIC GRAVITY	0.8
FLAMMABILITY	Combustible Liquid
FLASH POINT	>63°C



2051620



Providing hygiene service solutions since 1934