



HI FLUX EXCEL

Alkaline Membrane Cleaner



FEATURES

- Premium sequestering ability
- Unique buffering system
- Improved soil removal
- Compatible with chlorine at CIP strength
- HALAL, KOSHER approved

AREAS OF USE

- All types of membranes
- Fat and protein removal
- Hot & cold processing areas

DESCRIPTION

HI FLUX EXCEL is a blended alkaline solution containing surface wetting and premium biodegradable sequestering agent.

DIRECTIONS FOR USE

HI FLUX EXCEL is used at concentrations between 0.2-0.4% v/v (0.2-0.4L per 100L water). Typical CIP pH target is 10.8-11.0 at 50° C. Circulate a diluted detergent solution for 20-30 minutes, depending on the degree of soiling. Rinse with water after use.

Please note that all membrane cleaning must be carried out in accordance with the membrane manufacturer's guidelines, recommended limits of pH, temperature and exposure time should be followed.

Consult your Jasol representative for further information.

SAFETY INFORMATION

HI FLUX EXCEL is classified as Hazardous according to the GHS.

HI FLUX EXCEL is classified as Dangerous Goods according to the ADG Code (7th Ed).

HI FLUX EXCEL is a Scheduled Poison according to the SUSMP.

Avoid contact with eyes and skin. Refer to SDS for further information.

FIRST AID INFORMATION

If poisoning occurs contact a doctor or **Poisons Information Centre Australia, Phone 13 11 26.** If swallowed do NOT induce vomiting. Wash out mouth thoroughly with water and seek immediate medical attention. If in eyes, hold eyelids apart and flood with water for at least 15 minutes. If on skin, remove contaminated clothing and wash affected area with running water. Seek immediate medical attention.

24 HOUR TOLL FREE EMERGENCY PHONE NO: 1800 629 953

PRODUCT ENQUIRIES

Customer Service: **1800 334 679** jasolcsteam@gwf.com.au

For further information regarding product safety and handling, refer to the Safety Data Sheet and product label.

PHYSICAL & CHEMICAL PROPERTIES

FORM Clear Liquid
COLOUR Straw
ODOUR Odourless
pH >13.5
SPECIFIC GRAVITY 1.325

FLAMMABILITY Not Flammable

15L 2170635 200L 2170637





Last Modified: 20/02/2025 Revision: 2.0 Page 1