



JASOL'S GLAZE RANGE FLOOR CARE & MAINTENANCE PROCEDURE

Achieve stunning, long-lasting results with Jasol's three-step floor care system, designed for commercial environments and beyond. **GLAZE STRIP**, a powerful floor stripper that removes old waxes, polymers, and finishes from a wide range of surfaces, including vinyl, marble, and terrazzo—preparing your floors for a fresh start. **GLAZE REFLECTION**, a metallised polymer sealer finish that delivers a spectacular gloss and "wet look" in just two coats. For daily cleaning and ongoing shine, **GLAZE CLEAN & BUFF**, a concentrated blend of detergents and thermoplastic polymers that cleans, polishes, and restores floors to their full beauty.

Our Glaze Floor Care Range is ideal for shopping centres, supermarkets, restaurants, hospitals, hotels, and more, this programme ensures your floors always look their best.













JASOL'S GLAZE RANGE FLOOR CARE & MAINTENANCE PROCEDURE

First Impressions Count

A clean, polished floor sets the standard for your workplace. Dull, dirty, or scuffed surfaces can negatively impact perceptions of your business. For vinyl and linoleum floors, applying a quality finish protects the original gloss, enhances appearance, and improves safety with higher slip resistance. Effective floor care involves:

- Stripping: Remove old coatings carefully to avoid damage.
- **Sealing:** Ensure the floor is ready to accept a seal for lasting protection.
- Polishing & Maintenance: Use neutral pH cleaners and maintain regularly to preserve shine and durability.

Always match cleaning methods to your floor type. Proper equipment and procedures are essential for optimal results.

For detailed procedures on stripping, sealing, polishing, and maintaining hard floors, refer to the attached guidelines.

PREPARATION

- Wear PPE and place 'wet floor' signage.
- Read Product Information sheet and SDS.
- Remove furniture and obstructions.
- Sweep or vacuum floor thoroughly.
- Gather and prepare equipment: chemical, mop, buckets, black pads, Doodlebug/ Eager Beaver, autoscrubber or swing machine.

EQUIPMENT CHECKLIST

- Broom or static control mop
- Buckets (minimum two, clean)
- Mops (at least one clean; new mops pre-soaked in hot water)
- Slow speed floor machine / floor polishing machine / buffing machine (low/high speed)
- Hot water supply
- Black stripping pads (for stripping)
- Red buffing pads (for buffing)
- Blue scrubbing pads (for maintenance)
- Doodle bug (for edges and recessed areas)
- Wet/dry vacuum cleaner (optional for solution pick-up)
- Eager Beaver (floor model)











JASOL'S GLAZE RANGE FLOOR CARE & MAINTENANCE PROCEDURE

1. FLOOR STRIPPING – Using GLAZE STRIP

Dilution: Mix at 1:10 with water.

- 1. Apply generously to floor.
- 2. Allow 5-10 minute dwell time.
- 3. Scrub using auto scrubber or swing machine with black pad.
- 4. Detail edges with a doodlebug.
- 5. Remove slurry using wet vac or mop.
- 6. Rinse floor 2-3 times with clean water.
- 7. Allow floor to dry completely.



LONG-TERM PROGRAM

DAILY:

Clean with Glaze
Clean & Buff.

WEEKLY:

Buff as needed.

EVERY 3-6 MONTHS:

Apply a top-up coat of Glaze Reflection.

EVERY 6-12 MONTHS:

Complete strip & seal cycle.

2. FLOOR SEALING – Using GLAZE REFLECTION

- 1. Ensure floor is completely dry.
- 2. Apply 2 thin, even coats with a clean finish mop.
- 3. Allow each coat to dry for up to 30 minutes.
- 4. For high gloss, buff using low-speed or high-speed machine.
- 5. In cold weather, allow 2–3 days curing before buffing.



3. MAINTENANCE - Using GLAZE CLEAN & BUFF

Dilution:

Manual mopping: 1:60 with water

Auto scrubber: 1:40 with water

Daily: Clean floors using diluted solution. No rinse required.

Weekly: Buff floors to maintain gloss and protect seal.







